



**SILVERSTONE**<sup>®</sup>  
Designing Inspiration



**115XS**

**115XP**

**AR09**

Superior **2U** server thermal solution  
for Intel LGA115X

**SPECIAL FEATURES**

- Three 6mm heat-pipes and aluminum fins for excellent heat conducting efficiency
- Heat-pipe direct contact (HDC) technology
- 60mm dual ball bearing PWM fan
- Includes spring screw bracket with backplane (AR09-115XS)
- Push-Pin design for convenient installation (AR09-115XP)
- Intel LGA1150/1151/1155/1156 compatible



**SPECIFICATIONS**

Model No.	SST-AR09-115XS	SST-AR09-115XP	Noise	18.02 ~ 42.5dBA
Net Weight	295g (without fan)	215g (without fan)	Bearing	Dual ball bearing
			Voltage Rating (V)	12V
Material	Copper heat pipes with aluminum fins		Start voltage (V)	9.6V
Application	Intel LGA1150/1151/1155/1156		Max air pressure	0.33 ~ 4.83mmH2O
Heat Pipe Type	Ø6mm heat-pipe x 3		Air flow (CFM)	6.7 ~ 27.9CFM
Cooling System	60mm x 60mm x 25mm fan		Speed (R.P.M.)	1200 ~ 5000RPM
Dimension	88mm (W) x 66mm (H) x 88mm (D) (with Fan) (AR09-115XS)		Life expectancy (hrs)	70,000 hours
	93mm (W) x 66mm (H) x 93mm (D) (with Fan) (AR09-115XP)			

**Taiwan Headquarters**

12F., No.168, Jiansong Rd.,  
Zhonghe Dist., New Taipei City 235,  
Taiwan R.O.C.  
Tel: + 886-2-8228-1238 / Fax: + 886-2-8228-7123  
For sales and purchasing: sales@silverstonetek.com

**USA**

13626 Monte Vista Ave. Unit #A,  
Chino, CA 91710,  
USA  
Tel: + 1-909-465-9596 / Fax: + 1-909-465-9569  
For General Questions/Sales: usasales@silverstonetek.com

**Europe**

Brandstücken 27,  
D-22549 Hamburg,  
Germany  
Tel: + 49-40-675931-0 / Fax: + 49-40-675931-66  
For sales and purchasing: sales.eu@silverstonetek.de