



SILVERSTONE[®]
Designing Inspiration



115XS

AR10

Superior **3U** server thermal solution
for Intel LGA115X



115XP

SPECIAL FEATURES

- Three 6mm heat-pipes and aluminum fins for excellent heat conducting efficiency
- Heat-pipe direct contact (HDC) technology
- 70mm dual ball bearing PWM fan
- Includes spring screw bracket with backplane (AR10-115XS)
- Push-Pin design for convenient installation (AR10-115XP)
- Intel LGA1150/1151/1155/1156 compatible



SPECIFICATIONS

Model No.	SST-AR10-115XS	SST-AR10-115XP	Noise	18.07 ~ 39.03dBA
Net Weight	320g (without fan)	240g (without fan)	Bearing	Dual ball bearing
			Voltage Rating (V)	12V
Material	Copper heat pipes with aluminum fins		Start voltage (V)	9.6V
Application	Intel LGA1150/1151/1155/1156		Max air pressure	0.08 ~ 4.83mmH ₂ O
Heat Pipe Type	Ø6mm heat-pipe x 3		Air flow (CFM)	4.83 ~ 19.49CFM
Cooling System	70mm x 70mm x 15mm fan		Speed (R.P.M.)	500 ~ 4000RPM
Dimension	88mm (W) x 79mm (H) x 88mm (D) (with Fan) (AR10-115XS)		Life expectancy (hrs)	70,000 hours
	93mm (W) x 79mm (H) x 93mm (D) (with Fan) (AR10-115XP)			

Taiwan Headquarters

12F., No.168, Jiansong Rd.,
Zhonghe Dist., New Taipei City 235,
Taiwan R.O.C.

Tel: + 886-2-8228-1238 / Fax: + 886-2-8228-7123
For sales and purchasing: sales@silverstonetek.com

USA

13626 Monte Vista Ave. Unit #A,
Chino, CA 91710,
USA

Tel: + 1-909-465-9596 / Fax: + 1-909-465-9569
For General Questions/Sales: usasales@silverstonetek.com

Europe

Brandstücken 27,
D-22549 Hamburg,
Germany

Tel: + 49-40-675931-0 / Fax: + 49-40-675931-66
For sales and purchasing: sales.eu@silverstonetek.de