



SILVERSTONE[®]
Designing Inspiration

ES02-PCIe

2.4GHz

wireless computer power
and reset remote switch

2.4GHz receiver PCIe card included



FEATURES

- Control your computer from anywhere in the room using 2.4GHz RF remote
- 2.4GHz receiver PCIe card included
- Works as far away as twenty meter
- Includes power / reset switch Y cable
- Includes optional low profile expansion slot cover
- Integrated PC speaker on receiver assist in providing auditory feedback while in use



SPECIFICATIONS

Adapter card

| | |
|---------------------|--|
| Adapter form factor | Low profile PCIe x1 |
| Operation frequency | 2.4GHz |
| EIRP | 3.76dBm (Measured max) |
| Operating range | 20 meter (Free space) |
| Environment | Operating temperature: 0°C ~ 40°C (32°F ~ 104°F) Storage temperature: -40°C ~ 70°C (-40°F ~ 158°F) Operating humidity: 10% ~ 90% non-condensing Storage humidity: 5% ~ 90% non-condensing |
| Net Weight | 29.6g |
| Dimension | 120mm (W) x 21mm (H) x 68mm (D) 4.72" (W) x 0.83" (H) x 2.68" (D) |

Remote control

| | |
|---------------------|---|
| Operation frequency | 2.4GHz |
| EIRP | 3.76dBm (Measured max) |
| Operating range | 20 meter (Free space) |
| Battery type | CR2032 (Lithium manganese button battery) |
| Nominal voltage | DC 3.0V |
| Battery environment | Operating temperature: -20°C ~ 70°C (-4°F ~ 158°F) Storage temperature: 10°C ~ 40°C (50°F ~ 104°F) |



Taiwan Headquarters

12F., No.168, Jiankang Rd.,
Zhonghe Dist., New Taipei City 235,
Taiwan R.O.C.
Tel: + 886-2-8228-1238 / Fax: + 886-2-8228-7123
For sales and purchasing: sales@silverstonetek.com

USA

13626 Monte Vista Ave. Unit #A,
Chino, CA 91710,
USA
Tel: + 1-909-465-9596 / Fax: + 1-909-465-9569
For General Questions/Sales: usasales@silverstonetek.com

Europe

Brandstücken 27,
D-22549 Hamburg,
Germany
Tel: + 49-40-675931-0 / Fax: + 49-40-675931-66
For sales and purchasing: sales.eu@silverstonetek.de