



Gemini 시리즈

GM400 1U Bronze

400W 1U 리던던트 Cybenetics Bronze 등급 파워 서플라이



400W












- 45°C 완전하게 연속적인 전원 출력 상태에서 400+400W 24 시간 동안 문제없이 작동하는 성능
- 1U 리던던트 폼 팩터로 106mm(W) x 41.5mm(H) x 260mm(D)의 크기
- 1+1 중복 구성
- 핫 스와퍼블 설계
- 편리한 풀아웃 핸들 바
- 업계를 선도하는 신뢰성

사양

제품 번호	SST-GM400-1UB
색	실버
MTBF	100,000 시간
작동 온도	0°C ~ 45°C
냉각 시스템	40mm DC 팬
소음 레벨	52 dBA
보호	과전류보호 과전압 보호 저전압 보호 회로단락 보호
커넥터	1 x 24 / 20-핀 메인보드 커넥터 1 x 4 -핀 EPS / ATX 12V 커넥터 1 x 8 -핀 EPS / ATX 12V 커넥터 3 x SATA 커넥터 5 x 4-핀 주변장치 커넥터 1 x 4-핀 플로피 커넥터 1 x 2-Pin +5V TTL 신호 커넥터 1 x 갈색 / 백색 전원 1 LED 1 x 빨간색 / 흰색 전원 2 LED 1 x 녹색 / 흰색 전원 / 모듈 식 시스템 LED
치수	123mm (W) x 41.5mm (H) x 270mm (D) (브라켓 불포함 케이스) 106mm (W) x 41.5mm (H) x 260mm (D) (브라켓 포함 케이스, 손잡이 X) 50mm (W) x 40mm (H) x 220mm (D) (손잡이 없이 모듈러만)



Connectors / Cable

Photo	Type	Connector quantity per cable	Cable quantity	Length
	24 / 20-Pin motherboard connector	1	1	500mm
	CPU 8P connector	1	1	500mm
	CPU 4P connector	1	1	500mm
	Peripheral 4P connector	3	1	500mm 150mm 150mm
	Peripheral 4P connector	2	1	500mm 150mm
	4P Floppy connector	1	1	150mm
	SATA connector	3	1	500mm 150mm 150mm
	power 1 LED connector	1	1	BROWN / WHITE 900mm
	power 2 LED connector	1	1	RED / WHITE 900mm
	power / modular system LED connector	1	1	GREEN / WHITE 900mm
	2-Pin +5V TTL signal connector	1	1	Power Module/System Status LED TTL Signal Cable 900mm